



UM60 Mini-BTE

Linear
General Purpose, Broadband Response


HEARING AID FEATURES

- Powerful telecoil
- Gain tied to Maximum Power Output
- Two controls provide fitting flexibility:
T - Low-cut Tone
P - Power
- Controls continuously adjustable with end stops
- Surface Mount Technology
- Volume Control: numbered 1 (low) to 4 (high)
- M-T-O Switch: 3 positions Microphone–Telecoil–Off
- Slim mini-housing
- Unfiltered earhook
- Battery size: 13
- Fitting is supported by NOAH-compatible Unifit or Standalone Unifit

OPTIONS

- Filtered earhook
- Child-sized earhook
- Brown or gray housing

SUITABLE FOR FITTING MILD TO MODERATELY SEVERE HEARING LOSSES




ANSI S3.22-1996 TECHNICAL DATA


Frequency Range	200-5800 Hz	
P (Power) Control Setting	-15	0
Peak Gain	40 dB*	53 dB
Peak Output	111 dB	126 dB
Reference Test Gain	41 dB	
HF Average Gain (50 dB in)	32 dB*	50 dB
HF Average SSPL90	104 dB	118 dB
Typical Battery Life (Zinc Air Premium)	485 h	320 h
Current Drain at RTP	0.6 mA	0.9 mA
Telephone Magnetic Field Simulator		
HFA SPLITS	91 dB	
STS SPLITS	-10 dB	
Equivalent Input Noise at RTP typical 21 dB	25 dB	
Total Harmonic Distortion at RTP		
500 Hz	not applicable	
800 Hz	typical 2%	< 8%
1600 Hz	typical 2%	< 8%

*at P=-15, reduced input level was used to avoid saturation


UM60 MINI-BTE ANSI SPECIFICATIONS




Input sound pressure level: 90 dB
Volume Control: full on
T: N




Input sound pressure level: 60 dB
Volume Control: RTP
P: 0



Input sound pressure level: 50 dB
Volume Control: as shown
T: N **P: 0**



Input sound pressure level: 60 dB
Volume Control: RTP
"A" unfiltered, standard
"B" filtered, optional



Input: 31.6 mA/m
Volume Control: RTP
T: N **P: 0**

TEST CONDITIONS

RTP-ANSI: Reference Test Position of the Volume Control: 3
BATTERY: 13 Zinc Air Premium
SOURCE: Voltage 1.3 V
Impedance 6 Ohms
EARHOOK: Unfiltered
TUBING: Length 25 mm,
Inside Diameter 1.93 mm
Refer to: "Summary of Test Conditions and Limits" for more details.

AID MARKING: UM60

COMPLIANCE

Our products are designed to meet all of the limits required when tested in accordance with the applicable standard.

REFERENCES

ASA: Acoustical Society of America,
ANSI S3.22-1996
FDA: Food and Drug Administration,
Part 801

We reserve the right to change specification data without notice as improvements are introduced.

This product is manufactured under the protection of U.S. Patent #4349082 & #5204917.

Caution: Hearing aids and batteries can be harmful if swallowed or improperly used.



U.S.A.

Plymouth, Minnesota
800 888 8882; 763 744 3300
fax 763 557 8828

CANADA

Cambridge, Ontario
800 265 8255; 519 650 9111
fax 800 949 6663

EUROPE

Bremen, Germany
49 421 43 87 90
fax 49 421 48 81 56

INTERNATIONAL

Kitchener, Ontario, Canada
519 895 0100
fax 519 895 2318

CORPORATE OFFICE

Kitchener, Ontario, Canada
877 492 6244; 519 895 0100
fax 519 895 0108

www.unitronhearing.com