



## UE10 Mini-BTE

**Output Compression  
High Power, Push-Pull, Broadband Response**


### HEARING AID FEATURES

- Powerful Push-Pull amplifier
- Three controls provide full fitting flexibility:  
C – Compression  
T – Active Low-cut Tone  
P – Power Control
- Controls continuously adjustable with end stops
- Powerful Telecoil
- Frequency Dependent Input Compression (FDC)
- Adjustable Compression Threshold range of 30 dB
- Low Harmonic Distortion
- Surface Mount Technology
- Volume Control numbered: 1 (low) to 4 (high)
- M-T-O Switch: 3 positions Microphone–Telecoil–Off
- Unfiltered earhook
- Battery size: 675
- Fitting is supported by NOAH-compatible Unifit or Standalone Unifit

### OPTIONS

- Direct Audio Input
- CROS/BiCROS
- Filtered earhook
- Child-sized earhook
- Brown housing

**SUITABLE FOR FITTING MODERATELY SEVERE TO PROFOUND HEARING LOSSES INCLUDING RECRUITMENT AND DISCRIMINATION PROBLEMS**



Fitting Guide




### ANSI S3.22-1996 TECHNICAL DATA


Frequency Range	280-6000 dB	
P (Power) Control Setting	-16	0
Peak Gain	68 dB*	69 dB
Peak Output	120 dB	136 dB
Reference Test Gain	45 dB	
HF Average Gain 50 dB in	61 dB*	62 dB
HF Average OSPL90	112 dB	122 dB
Typical Battery Life (Zinc Air Premium)	500 h	400 h
Current Drain at RTP	1.2 mA	1.5 mA
Telephone Magnetic Field Simulator		
HFA SPLITS	102 dB	
STS SPLITS	-3 dB	
Equivalent Input Noise at RTP typical 27 dB	< 30 dB	
Total Harmonic Distortion at RTP		
500 Hz	not applicable	
800 Hz	typical 3%	< 8%
1600 Hz	typical 3%	< 8%
(Data applicable at C=55)		
Attack Time	< 10 ms	
Release Time	100 ms	
Compression Ratio	20:1	

\*At lower Power Control setting, reduced input level was used to avoid saturation.


# UE10 MINI-BTE ANSI SPECIFICATIONS




Input sound pressure level: 90 dB  
Volume Control: full on  
T: N C: 55=On; 85=Off




Input sound pressure level: 50 dB  
VC: RTP  
C: 55 P: 0




Input at 2000 Hz  
VC: RTP  
T: N P: 0




Input sound pressure level: 50 dB  
VC: as shown  
T: N C: 55 P: 0



Input at 2000 Hz  
VC: as shown  
T: N C: 55 P: 0



Input sound pressure level: 50 dB  
Volume Control: RTP  
"A" unfiltered, standard  
"B" filtered, optional



Input: 31.6 mA/m  
VC: RTP  
T: N C: 55 P: 0

## TEST CONDITIONS

RTP-ANSI: Reference Test Position of the Volume Control: 3  
BATTERY: 13 Zinc Air Premium  
SOURCE: Voltage 1.3 V  
Impedance 3.5 Ohms  
EARHOOK: Unfiltered  
TUBING: Length 25 mm,  
Inside Diameter 1.93 mm  
Refer to: "Summary of Test  
Conditions and Limits"  
for more details.

## AID MARKING: UE10

## COMPLIANCE

Our products are designed to meet all of the limits required when tested in accordance with the applicable standard.

## REFERENCES

ASA: Acoustical Society of America,  
ANSI S3.22-1996  
FDA: Food and Drug Administration,  
Part 801

We reserve the right to change specification data without notice as improvements are introduced.

This product is manufactured under the protection of U.S. Patent #4349082 & #5204917.

Caution: Hearing aids and batteries can be harmful if swallowed or improperly used.



## CORPORATE OFFICE

Kitchener, Ontario, Canada  
877 492 6244; 519 895 0100  
fax 519 895 0108

## CANADA

Cambridge, Ontario  
800 265 8255; 519 650 9111  
fax 800 949 6663

## U . S . A .

Plymouth, Minnesota  
800 888 8882; 763 744 3300  
fax 763 557 8828

## INTERNATIONAL

Kitchener, Ontario, Canada  
519 895 0100  
fax 519 895 2318

## EUROPE

Bremen, Germany  
49 421 43 87 90  
fax 49 421 48 81 56

www.unitronhearing.com